



GelMaker® PH

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / March 26, 2012 / Rules and Regulation

Revision Date: 05-22-2018 Supersedes: None

PRODUCT & COMPANY IDENTIFICATION

Product Name: GelMaker® Powder Synonyms: Not available

INCI Name: Polvacrylate crosspolymer-6

CAS Number: 111286-86-3 Formula: Not available Product Form: Solid (powder)

Product Use: Cosmetic use Distributor: MakingCosmetics.com Inc. Address: 10800 231st Way NE

Redmond, WA 98053 (USA)

Phone / Fax: 425-292-9502 / 425-292-9601 Web: www.makingcosmetics.com

Emergency Telephone Number: 1-800-424-9300 (Chemtrec)

HAZARDS IDENTIFICATION

GHS Classification: Not classified **GHS Labeling:** Not classified

GHS Hazard Pictograms: None **GHS Hazard Statements:** None **GHS Precautionary Statements:** None

Potential Health Hazards: Fine dust clouds may form explosive mixtures with air. Handling and/or processing of

this material may generate a dust which can cause mechanical irritation of the eyes,

skin, nose and throat.

NFPA Ratings (704): Health n/a

n/a Flammability Reactivity n/a Specific Hazard n/a

COMPOSITION/INFORMATION ON INGREDIENTS

CAS No. Weight % Molecular Weight Component

111286-86-3 80-100% Polyacrylate N/A

crosspolymer-6

2-methylpropan-2-ol 1093099-09-2 1-5%

FIRST AID MEASURES

Irrigate eyes with a heavy stream of water for at least 15 to 20 minutes. Seek medical attention if irritation persists. Eyes:

Inhalation: Remove to fresh air. Seek medical attention if necessary.

Skin: Wash skin with soap and water. Seek medical attention if symptoms occur. Rinse mouth with diluted milk or water and seek medical attention immediately. Ingestion:

FIRE-FIGHTING MEASURES

Suitable (and unsuitable) Water spray, carbon dioxide, dry chemical or foam. Do not use direct water jet on burning extinguishing media: material.

Special protective equipment & precautions for firefighters:

Firefighters should wear full protective clothing including self-contained breathing apparatus.

Flash Points: Not available.

Specific hazards arising from the

chemical:

Carbon monoxide, carbon dioxide. Fine dust clouds may form explosive mixtures with air.

ACCIDENTAL RELEASE MEASURES





Personal precautions, protective equipment & emergency procedures: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.

Environmental precautions: Methods and material for containment and cleaning up:

Prevent entry into waterways, sewers, basements or confined areas. Pick up spilled material and containerize for recovery or disposal.

HANDLING & STORAGE

Precautions for safe handling:

Put on appropriate personal protective equipment (see Section 8). Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.

Conditions for safe storage, incl. any incompatibilities:

Containers should be kept closed in order to minimize contamination. Store in sealed original container. Make sure the material does not come into contact with substances listed as "Materials to Avoid".

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Component **Exposure Limits**

2-methylpropan-2-ol EH40/2005 WELs (United Kingdom (UK),

8/2007).

STEL: 462 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 308 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s).

TWA: Time Weighted Average over 8 hours of work. TLV: Threshold Limit Value over 8 hours of work.

REL: Recommended Exposure Limit PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit during x minutes. IDLH: Immediately Dangerous to Life or Health WEEL: Workplace Environmental Exposure Levels

Entity

CEIL: Ceiling

<u>Basis</u>

Personal Protection:

Safety glasses, goggles, or face shield recommended for eye protection. Eyes: Inhalation: Appropriate NIOSH approved respiratory protection may be worn.

Body: Gloves and protective clothing should be worn to prevent prolonged skin contact.

Other: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately

after handling the product.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Solid powder Odor: Mild, acrylic Taste: Not available

Color: White

<2 mm : 98% ; <150 μm : 25% ; <80 μm : 7% Granulometry:

3 to 6 [Conc. (% w/w): 2%] pН

Boiling Point: Not available Not available Melting Point:

Vapor Pressure: Not available Vapor Density: Not available **Evaporation Rate:** Not available Flammability: Not flammable Upper/lower Explosive Limit: Not available

Solubility: Dispersible in water Flash Point: Not available Density: 0.23 [not tapped]

10 STABILITY AND REACTIVITY





Reactivity: Stable under normal conditions. Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or

flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and

equipment before transferring material. Prevent dust accumulation.

Reactive or incompatible with the following materials: oxidizing materials Incompatible Materials:

Hazardous Decomposition Products: Under normal storage/use conditions hazardous decomp. products should not be produced.

TOXICOLOGICAL INFORMATION

LC50 Inhalation Gas: >10000 ppm 4 hours **Acute Toxicity**

(2-methylpropan-2-ol) LD50 Dermal: >2 g/kg LD50 Oral: 2733 mg/kg

No known significant effects or critical hazards

Eyes: Exposure to airborne concentrations above statutory or recommended exposure limits may cause

irritation of the eyes

Respiratory: Exposure to airborne concentrations above statutory or recommended exposure limits may cause

irritation of the nose, throat and lungs

Ingestion: No known significant effects or critical hazards Carcinogenicity: No known significant effects or critical hazards Teratogenicity: No known significant effects or critical hazards Germ Cell Mutagenicity: No known significant effects or critical hazards **Embryotoxicity:** No known significant effects or critical hazards Specific Target Organ Toxicity: No known significant effects or critical hazards No known significant effects or critical hazards Reproductive Toxicity: Respiratory/Skin Sensitization: No known significant effects or critical hazards

ECOLOGICAL INFORMATION

Ecotoxicity Acute EC50 5504000 ug/L Fresh water, Species: Daphnia - Daphnia magna, 6 to 24 hours, Exposure:

(2-methylpropan-2-ol)

Acute LC50 6410000 ug/L Fresh water, Species: Fish - Pimephales promelas - 32 days - 20mm -

0,114 g, Exposure: 96 hours

Persistence and Degradability: Not available

Bioaccumulative Potential: By analogy. Not readily biodegradable. This product shows a low bioaccumulation potential

Mobility in Soil:

Not available Not available

PBT and vPvB Assessment: Other Adverse Effects: Not available

DISPOSAL CONSIDERATIONS

Users should review their operations in terms of the applicable federal/national or local regulations and Waste Residues:

consult with appropriate regulatory agencies if necessary before disposing of waste product container.

Users should review their operations in terms of the applicable federal/national or local regulations and **Product Containers:**

consult with appropriate regulatory agencies if necessary before disposing of waste product container.

The information in section 13 is for the product as shipped. Use and/or alterations to the product may change the characteristics of

the material and alter the waste classification and proper disposal methods

14 TRANSPORT INFORMATION

DOT (Dept. of Transportation, USA): Not regulated TDG (Transportation of Dangerous Goods, Canada): Not regulated IMDG (International Maritime Dangerous Goods): Not regulated IATA (International Air Transport Association): Not regulated ICAO (International Civil Aviation Organization): Not regulated





15 REGULATORY INFORMATION

TSCA Inventory Status: Not listed

This product is not classified according to the EU regulations. Not applicable. DSCL (EEC):

WHMIS (Canada): Not controlled under WHMIS (Canada)

16 OTHER INFORMATION

Revision Date: 05-22-2018

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Compliance:

Standard 29 CFR 1910.1200

This information relates only to the specific material designated and may not be valid for such material used in Disclaimer:

combination with any other materials or in any other process. Such information is to be the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no

responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's

responsibility to satisfy himself as to the suitableness & completeness of such information for his own particular